

BATTERY STRAPPING TOOL FOR
POLYESTER STRAP WITH VIBRATION SEALING



NEW

ONE PUSH OPERATED

TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	300 mm • 11.8"
Width	150 mm • 5.9"
Height	160 mm • 6.3"
Weight	4,1 Kgs • 9 lbs
FEEDING	
Battery	14.8V-3.2 A/h LI-PO
PERFORMANCE	
Max. tension force	5500N
Tensioning speed	12mt/m
Sealing	Vibration sealing
Joint strength	80% of breaking strength*

* variable according to strap type

OPERATING MODES
Fully Automatic
Semi Automatic
Manual

With Fully Automatic Mode tensioning, welding and strap cutting are performed with only one push of a button.

MODEL			
CODE	TYPE	STRAP	THICKNESS
T259997	ITA25 / 16-19mm with one battery	PET 16 mm-5/8"	1.05 mm - 0.041"
		PET 19 mm-3/4"	0.8 mm - 0.031" ÷ 1,27 mm - 0.05"
T2599971	ITA25 / 16-19mm with one battery and charger	PET 16 mm-5/8"	1.05 mm - 0.041"
		PET 19 mm-3/4"	0.8 mm - 0.031" ÷ 1,27 mm - 0.05"
T2599972	ITA25 / 16-19mm with two batteries and charger	PET 16 mm-5/8"	1.05 mm - 0.041"
		PET 19 mm-3/4"	0.8 mm - 0.031" ÷ 1,27 mm - 0.05"

POLYESTER STRAP



POLYESTER STRAP



ITATOOLS s.r.l.

Via Rossini, 340 - 21042 Caronno Pertusella (VA) - ITALY • p.iva 05022340961

Tel.: +39.02.96450619 - Fax +39.02.9659747 • E-mail: info@itatools.it - www.itatools.com